

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
Please do not report the images to the
Image Problem Mailbox.

IN THE CLAIMS:

1. (currently amended) A bush cutting machine comprising:

an operation rod having a front end and a rear end;

a cutter blade mounted to the front end of the operation rod for undergoing rotation;

a prime mover mounted to the rear end of the operation rod for rotationally driving the cutter blade;

a throttle lever pivotally mounted with respect to the operation rod for controlling an opening degree of a throttle valve of the prime mover to adjust a rotational speed of the cutter blade;

a main wire having a first end connected to the throttle lever so that pivotal movement of the throttle lever pulls the main wire in a pulling direction from a standby condition to an operative condition;

a throttle wire having a first end connected to the throttle valve of the prime mover so that when the main wire is pulled in the pulling direction the throttle wire undergoes movement in the pulling direction from a standby condition to an operative condition to control the opening degree of the throttle valve;

a brake unit for stopping rotation of the cutter blade in a braking condition of the brake unit;

~~a main wire having a first end connected to the throttle lever and a second end;~~

~~a throttle wire having a first end connected to the throttle valve of the prime mover and a second end;~~

C/ a brake wire having a first end connected to the brake unit ~~and a second end;~~ and so that when the main wire is pulled in the pulling direction the brake wire undergoes movement in the pulling direction from a standby condition in which the brake unit is in the braking condition to an operative condition in which the brake unit is released from the braking condition to allow rotation of the cutter blade; and

a link mechanism actuated by operation of the throttle lever to adjust the degree of opening of the throttle valve of the prime mover and to release the brake unit from a the braking condition when each of the main wire, the throttle wire and the brake wire is in the operative condition, the link mechanism having a generally U-shaped relay member having a first lug portion connected to ~~the~~ a second end of the main wire and a second lug portion connected to ~~the~~ a second end of the throttle wire and ~~the~~ a second end of the brake wire, the first and second lug portions forming opposite and confronting leg portions of the U-shaped relay member.

2. - 4. (canceled)

5. (previously presented) A bush cutting machine according to claim 1; further comprising a handle mounted on the operation rod, and an operating lever unit mounted on the handle and serving as a grip of the handle; wherein the link mechanism is disposed in the operating lever unit.

C1
6. (previously presented) A bush cutting machine according to claim 5; wherein the link mechanism has a delay mechanism actuated by operation of the throttle lever such that the throttle valve opens with a time delay upon release of the brake unit from the braking condition.

7. - 10. (canceled)

11. (previously presented) A bush cutting machine according to claim 1; wherein the relay member undergoes linear reciprocating movement in accordance with movement of the main wire, the throttle wire, and the brake wire.

12. (previously presented) A bush cutting machine according to claim 6; wherein the delay mechanism comprises the second ends of the throttle and brake wires connected to the second lug portion of the relay member so that when the throttle lever is not operated, the second end of the throttle wire is spaced from the second lug portion at distance greater than a space between the second end of the brake wire and the second lug portion.

13. (currently amended) A bush cutting machine comprising:

a prime mover having a throttle valve;

a rotary cutter blade;

a transmission member for transmitting drive power from the prime mover to the cutter blade to rotationally drive the cutter blade;

C1
a throttle lever for controlling an opening degree of the throttle valve of the prime mover to adjust a rotational speed of the cutter blade;

a brake unit for stopping rotation of the cutter blade in a braking condition of the brake unit;

a generally U-shaped relay member mounted to undergo movement by actuation of the throttle lever to adjust the opening degree of the throttle lever and to release the brake unit from the braking condition, the relay member having a first portion and a second portion disposed opposite the first portion, the first and second portions defining confronting leg portions of the U-shaped relay member;

a first wire having a first end connected to the throttle lever and a second end connected to the first portion of the relay member so that pivotal movement of the throttle lever pulls the first wire in a pulling direction from a standby condition to an operative condition;

C/ a second wire having a first end connected to the throttle valve of the prime mover and a second end connected to the second portion of the relay member so that when the first wire is pulled in the pulling direction the second wire undergoes movement in the pulling direction from a standby condition to an operative condition to control the opening degree of the throttle valve; and

a third wire having a first end connected to the brake unit and a second end connected to the second portion of the relay ~~member~~. member so that when the first wire is pulled in the pulling direction the third wire undergoes movement in the pulling direction from a standby condition in which the brake unit is in the braking condition to an operative condition in which the brake unit is released from the braking condition to allow rotation of the cutter blade.

14. - 15. (canceled)

16. (previously presented) A bush cutting machine according to claim 13; wherein the relay member undergoes linear reciprocating movement in accordance with movement of the first wire, the throttle wire, and the brake wire upon actuation of the throttle lever.

17. (previously presented) A bush cutting machine according to claim 13; further comprising a tubular operation rod enclosing the transmission member; a handle mounted on the tubular operation rod; and an operating lever unit mounted on the handle and serving as a grip of the handle.

18. (previously presented) A bush cutting machine according to claim 17; wherein the relay member is disposed in the operating lever unit.

C¹
19. (previously presented) A bush cutting machine according to claim 18; further comprising a delay mechanism including the relay member and actuated by operation of the throttle lever such that the throttle valve opens with a time delay upon release of the brake unit from the braking condition.

20. (previously presented) A bush cutting machine according to claim 13; wherein the delay mechanism comprises the second ends of the second and third wires connected to the second portion of the relay member so that when the throttle lever is not operated, the second end of the second wire is spaced from the second portion of the relay member at distance greater than a space between the second end of the third wire and the second portion of the relay member.

21. (new) A bush cutting machine according to claim 1; further comprising biasing means for biasing each of the main wire, the throttle wire, and the brake wire to the corresponding standby condition.

22. (new) A bush cutting machine according to claim 13; further comprising biasing means for biasing each of the first wire, the second wire, and the third wire to the corresponding standby condition.

23. (new) A bush cutting machine comprising:

a prime mover having a throttle valve;

a rotary cutter blade;

a transmission member for transmitting drive power from the prime mover to the cutter blade to rotationally drive the cutter blade;

a throttle lever for controlling an opening degree of the throttle valve of the prime mover to adjust a rotational speed of the cutter blade;

a brake unit for stopping rotation of the cutter blade in a braking condition of the brake unit;

a relay member mounted to undergo movement by actuation of the throttle lever to adjust the opening degree of the throttle lever and to release the brake unit from the braking condition;

a first wire having a first end connected to the throttle lever and a second end connected to the first portion of the relay member so that pivotal movement of the throttle lever pulls the first wire in a pulling direction from a standby condition to an operative condition;

C1
a second wire having a first end connected to the throttle valve of the prime mover and a second end connected to the second portion of the relay member so that when the first wire is pulled in the pulling direction the second wire undergoes movement in the pulling direction from a standby condition to an operative condition to control the opening degree of the throttle valve; and

a third wire having a first end connected to the brake unit and a second end connected to the second portion of the relay member so that when the first wire is pulled in the pulling direction the third wire undergoes movement in the pulling direction from a standby condition in which the brake unit is in the braking condition to an operative condition in which the brake unit is released from the braking condition to allow rotation of the cutter blade.

24. (new) A bush cutting machine according to claim 23; further comprising biasing means for biasing each of the first wire, the second wire, and the third wire to the corresponding standby condition.